



Omipay Web API

Author	Max.Wong
Create Date	2017-8-31
Version	v2.0

Catalog

1 .	Rules.....	2
1.1	Protocol Rules.....	2
1.2	Parameter Rules.....	2
1.3	Signature verification.....	2
2 .	API List.....	4
2.1	Get current exchange rate.....	4
2.2	Make QRCode Order.....	5
2.3	Make JSAPI Order.....	7
2.4	Make Scan Order.....	9
2.5	Query Order Status.....	11
2.6	Payment Success Notification	13
2.7	Refund.....	14
2.8	Query Refund	16
2.9	WeChat Client Login.....	18

1 . Rules

1.1 Protocol Rules

Transafer Mode	HTTPS
Submit Mode	POST/GET
Receive Data Format	Json
Text Encoding	UTF-8
Sign Algorithm	MD5
Data Sending Format	Sending data as URL parameter
Http Header	ContentType=application/json
Expiring	Transaction expires in 5 minutes

1.2 Parameter Rules

1) Amount

Amount uses the smallest unit of transaction currency, must be integer value.

e.g. amount 100 of currency AUD would be equivalent to A\$1.00.

2) Currency

The only currency type we support is AUD (Australian dollar).

3) Time zone

System time zone is EST (East Standard Time).

4) Timestamp

Convert current UTC time to milliseconds.

5) Nonce string

The random string witch length in 10-32 characters, allows the characters in a-z | A-Z | 0-9.

6) Payment platform

Omipay supports the payment platforms below:

Platform name	The value of parameter <i>platform</i>
Wechat Pay	WECHATPAY
Alipay	ALIPAY

7) language

Omipay WebAPI supports the languages below:

Language	The value of parameter <i>language</i>
English	EN
Simplified Chinese (Default)	CHS

1.3 Signature verification

1) Parameters

The parameters for verifying as below:

Name	Type	Description
m_number	String	Merchant number, can be found in merchant background system.
timestamp	Long	Time stamp, refer to <i>Timestamp</i> in <i>Parameter Rules</i>
nonce_str	String	Random string, refer to <i>Nonce string</i> in <i>Parameter Rules</i>

secret_key	String	API Secret key of merchant, acquired from merchant background system. This parameter is for private, don't let it shown in any public place.
------------	--------	--

2) Generate signature

① Concatenate all the parameters above like this:

`m_number×tamp&nonce_str&secret_key`

Make sure it's in the correct order.

② Use the concatenated string to make a signature string with MD5 algorithm, and then turn it into uppercase.

③ Put the signature string as a part of the query parameters, and then call the web api.

e.g.:

The parameters below:

m_number	123456
timestamp	1482812036067
nonce_str	313644f42ecd4758b5e23b80e86efdc4
secret_key	0af61531c6c04ac4ac910d0cd59e6238

The concatenated string below:

123456&1482812036067&313644f42ecd4758b5e23b80e86efdc4&0af61531c6c04ac4ac910d0cd59e6238

The code of making sign string below:

C#:

```
var originString =
"123456&1482812036067&313644f42ecd4758b5e23b80e86efdc4&0af61531c6c04ac4ac910d0cd59e6238";
var md5 = MD5.Create();
var bs = md5.ComputeHash(Encoding.UTF8.GetBytes(originString));
var sb = new StringBuilder();
foreach (byte b in bs)
{
    sb.Append(b.ToString("x2"));
}
originString = sb.ToString().ToUpper();
```

PHP:

```
$originString =
'123456&1482812036067&313644f42ecd4758b5e23b80e86efdc4&0af61531c6c04ac4ac910d0cd59e6238';
$sign = strtoupper(md5($originString));
```

Get the signature string:

`sign="516A3B52F9C8897F52239B19CD8A499"`

and then put it into the parameter string, we can get the parameter below:

`m_number=123456×tamp=1482812036067&nonce_str=313644f42ecd4758b5e23b80e86efdc4&sign=8516A3B52F9C8897F52239B19CD8A499`

Use this string for signature verifying.

2 . API List

2.1 Get current exchange rate

- Description :

Get the current exchange rate of AUD to CNY, which is provided by WeChat, refreshes in a day. This exchange rate is only for reference.

- API address:

<https://www.omipay.com.au/omipay/api/v2/GetExchangeRate>

- Parameters (except the sign verifying parameters, all the APIs are as the same.)

Field	Type	Example	Description
currency	String	AUD	The currency code which follows the ISO-4217 standard.
base_currency	String	CNY	
platform	String	WECHATPAY	Not mandatory, defaults <i>WECHATPAY</i>
language	String	EN	Not mandatory, defaults <i>CHS</i>

- Success returns:

Field	Type	Example	Description
return_code	String	SUCCESS	When execute succeed, returns SUCCESS, it shows the result of API execution.
rate	Decimal	5.01540000	Current exchange rate
platform	String	WECHATPAY	

- Fail returns:

Field	Type	Example	Description
return_code	String	FAIL	When execute failed, returns FAIL
error_code	String	SYSTEM_ERROR	Code of error
error_msg	String	System error.	Description of error

Error code list:

Error Code	Description
PARAMETER_INVALID	Invalid parameters, may caused by mandatory parameter missing, or parameter data type not correct.
SIGN_TIMEOUT	Time stamp is expired. The timestamp is less for more than 5 minutes to server time.
MERCHANTNO_INVALID	Merchant number is invalid. Please check the merchant

	number from merchant background system.
SIGN_ERROR	Signature check failed. Please check the signature string.
SYSTEM_ERROR	System unhandled error.

- Request example:

<https://www.omipay.com.au/omipay/api/v2/GetExchangeRate?>

m_number=123456×tamp=1482812036067&nonce_str=313644f42ecd4758b5e23b80e86efdc4&sign=8516A3B52F9C8897F52239B19CD8A499¤cy=AUD&base_currency=CNY

- Success returns example:

```
{
  "return_code": "SUCCESS",
  "rate": 5.01540000
}
```

- Fail returns example

```
{
  "return_code": "FAIL",
  "error_code": "SIGN_TIMEOUT",
  "error_msg": "Sign time out."
}
```

2.2 Make QRCode Order

- Description:

QRCode order suits for the scene of non-WeChat client web based payment. Merchant can call this API to get a string for payment, and then show this string to customer as a QRCode; Customer would scan this QRCode with WeChat to call the WeChat Payment function.

- API address:

<https://www.omipay.com.au/omipay/api/v2/MakeQROrder>

- Parameters:

Parameter	Type	Example	Description
order_name	String	Test_Order	The simple order information.
currency	String	AUD	Currency code of the order.
amount	int	100	Order amount in the base unit of the currency of order. Refers to section 1.2. e.g. if currency = AUD, then 100 means A\$1.00

notify_url	String		Notification URL for transaction success. When this order is pay succeed, will send a notification to such URL. Refers to section 2.6.
out_order_no	String		Out order number. The notification data of transaction would include this field. So, it best be unique, in order to identify the order.
platform	String	WECHATPAY	payment platform of this order.
language	String	EN	Not mandatory, defaults <i>CHS</i> .

- Success returns:

Field	Type	Example	Description
return_code	String	SUCCESS	SUCCESS
order_no	String		Omipay order number, 32 characters length.
qrcode	String		String for QRCode.
pay_url	String		The url of common payment page. When order is created, may redirect to this url to show the payment QRCode. * Access this page is also needs signing, the sign algorithm is same to other methods.

- Fail returns:

Field	Type	Example	Description
return_code	String	FAIL	FAIL
error_code	String	SYSTEM_ERROR	Code of error
error_msg	String	System error.	Description of error

Error Code list:

Error Code	Description
PARAMETER_INVALID	Invalid parameters.
SIGN_TIMEOUT	Time stamp expires.
MERCHANTNO_INVALID	Merchant number is invalid.
SIGN_ERROR	Signature check failed.
SYSTEM_ERROR	System unhandled error.

- Request example:

<https://www.omipay.com.au/omipay/api/v2/MakeQRCode?>

m_number=123456×tamp=1482812036067&nonce_str=313644f42ecd4758b5e23b80e86efdc4&sign=8516A3B52F9C8897F52239B19CD8A499&order_name=Test_Order&amount=100¬ify_url=http://your_site.com/receive_notify.html&out_order_no=SEORD000001

- Addition comments:

The flow of QRCode payment:

- 1) Merchant create order in Web or PC Online-Store;
- 2) Call Omipay MakeQRCodeOrder API;
- 3) Generate QRCode with the *qrcode* string of API returns, and then show it to customer in application interface;
OR: Redirect to *pay_url* and show the QRCode.
- 4) Customer scan this QRCode with WeChat/Alipay APP on mobile phone.
- 5) Customer finish the payment.
- 6) Omipay send transaction notification data to merchant.

- Success returns example:

```
{
  "return_code": "SUCCESS",
  "order_no": "bc112874260946a2af2b7107825e6ce2",
  "qrcode" : "..... "
}
```

- Fail returns example:

```
{
  "return_code": "FAIL",
  "error_code": "SIGN_TIMEOUT",
  "error_msg": "Sign timeout."
}
```

- Description of payment page:

- 1) When API returns, may lead the browser redirect to the *pay_url* address. Which page shows the information of order and the payment QRCode. Customer scans this QRCode with Alipay/Wechatpay app in mobile phone to finish the transaction. When payment is done, browser would redirect to the *redirect_url* address which in the call parameter.

- 2) For accessing the *pay_url*, the following parameters are required.

Field	Type	Example	Description
m_number	String		
timestamp	String	1482812036067	Time stamp, refer to <i>Timestamp</i> in <i>Parameter Rules</i>
noncestring	String		Random string, refer to <i>Nonce string</i> in <i>Parameter Rules</i>
sign	String		Sign string
redirect_url	String		Browser will redirect to such url when payment done.

2.3 Make JSAPI Order

- Description:

JSAPI order suits for the scenes below:

- 1) WeChat web browser based payment. Merchant could call this API to get a URL for payment, and then lead customer to access this URL to pay.
- 2) Common pay QRCode for transaction. Merchant could use the pay_url generate a QRCode, and show it to customer. Customer could scan this code with either Wechat or Alipay client app on mobile phone to pay.

- API address:

<https://www.omipay.com.au/omipay/api/v2/MakeJSAPIOrder>

- Parameters:

Parameter	Type	Example	Description
order_name	String	TEST_ORDER	The simple order information.
currency	String	AUD	Currency code of the order.
amount	int	100	Order amount in the base unit of the currency of order. Refers to section 1.2. e.g. if currency = AUD, then 100 means A\$1.00
notify_url	String		Notification URL for transaction success. When this order is pay succeed, will send a notification to such URL. Refers to section 2.6.
redirect_url	String		Redirecting URL for transaction success. When this order is pay succeed, web browser will auto redirect to such URL.
out_order_no	String		Out order number. The notification data of transaction would include this field. So, it best be unique, in order to identify the order.
language	String	EN	Not mandatory, defaults <i>CHS</i> .

- Success returns:

Field	Type	Example	Description
return_code	String	SUCCESS	SUCCESS
order_no	String		Omipay order number, 32 characters length.
pay_url	String		URL for payment. Merchant should lead user to access this URL.

- Fail returns:

Field	Type	Example	Description
return_code	String	FAIL	FAIL
error_code	String	SYSTEM_ERROR	Code of error
error_msg	String	服务器错误	Description of error

Error Code list:

Error Code	Description
PARAMETER_INVALID	Invalid parameters.
SIGN_TIMEOUT	Time stamp expires.
MERCHANTNO_INVALID	Merchant number is invalid.
SIGN_ERROR	Signature check failed.
SYSTEM_ERROR	System unhandled error.
WECHAT_STORE_NOT_EXISTS	This merchant don't have the WESTORE type organization.

- Request example:

<https://www.omipay.com.au/omipay/api/v2/MakeJSAPIOrder?>

m_number=123456×tamp=1482812036067&nonce_str=313644f42ecd4758b5e23

b80e86efdc4&sign=8516A3B52F9C8897F52239B19CD8A499&order_name=TEST_ORDE

R&redirect_url=http://your_site.com/redirect_to.html&amount=100¬ify_

url=http://your_site.com/receive_notify.html&out_order_no=SEORD000001&l

anguage=EN

- Success returns example:

```
{
  "return_code": "SUCCESS",
  "order_no": "bc112874260946a2af2b7107825e6ce2",
  "pay_url" : "....."
}
```

- Fail returns example:

```
{
  "return_code": "FAIL",
  "error_code": "SIGN_TIMEOUT",
  "error_msg": "Sign timeout."
}
```

2.4 Make Scan Order

- Description:

Scan order is suits the scene of local payment. Customer shows the Payment code in WeChat Wallet/Alipay client, merchant scans the code by POS device, AND then call API to create order.

- API address:

<https://www.omipay.com.au/omipay/api/v2/MakeScanOrder>

- Parameters:

Parameter	Type	Example	Description
order_name	String	TEST_ORDER	The simple order information.
currency	String	AUD	Currency code of the order.
amount	int	100	Order amount in the base unit of the currency of order. Refers to section 1.2. e.g. if currency = AUD, then 100 means A\$1.00
notify_url	String		Notification URL for transaction success. When this order is pay succeed, will send a notification to such URL. Refers to section 2.6.
qrcode	String		Customer's payment QRCode.
pos_no	String		POS Device number.
out_order_no	String		Out order number. The notification data of transaction would include this field. So, it best be unique, in order to identify the order.

- Success returns:

Field	Type	Example	Description
return_code	String	SUCCESS	SUCCESS: Pay succeed
order_no	String		Omipay order number, 32 characters length.
out_order_no	String		Out order number.
order_time	String		Order pay time, in format of yyyyMMddHHmmss

- Fail returns:

Field	Type	Example	Description
return_code	String	FAIL	FAIL
error_code	String	SYSTEM_ERROR	Code of error
error_msg	String	Server error	Description of error
order_no	String		If error_code = "USERPAYING", then returns this field. Refers to <i>Addition comments</i> .

Error Code list:

Error Code	Description
PARAMETER_INVALID	Invalid parameters.
SIGN_TIMEOUT	Time stamp expires.
MERCHANTNO_INVALID	Merchant number is invalid.
SIGN_ERROR	Signature check failed.
SYSTEM_ERROR	System unhandled error.
ORDER_PAID	This order is already paid.
POS_NOT_REGISTERED	POS device is not registered.
NOT_ENOUGH	Not enough fee balance in user's WeChat Wallet.

CARD_NOT_SUPPORT	User' s card type is not supported by WeChat Pay.
ORDER_CLOSED	Order is already closed.
QRCODE_EXPIRED	QRCode is expired.
QRCODE_ERROR	QRCode error.
AMOUNT_INVALID	Amount is invalid. When amount exceeds the up limit of payment platform, or exceeds the min amount of payment platform, this error occurs.

- Request example:

<https://www.omipay.com.au/omipay/api/v2/MakeScanOrder?>

m_number=123456×tamp=1482812036067&nonce_str=313644f42ecd4758b5e23

b80e86efdc4&sign=8516A3B52F9C8897F52239B19CD8A499&order_name=Test_Order&

amount=100&¬ify_url=http://your_site.com/receive_notify.html&qrcode=123abc123&pos_no=posno_123&out_order_no=SEORD000001&language=EN

- Addition comments:

The flow of Scan payment:

- 1) Merchant create the order in POS System, and show the amount of such order to customer;
- 2) Customer show the Payment QRCode of WeChat Wallet;
- 3) Merchant scan the QRCode with POS Device, and call *MakeScanOrder* API to create payment order.
- 4) Omipay server solves the request, meanwhile, merchant waits for the result of order.
- 5) If Omipay returns the *SUCCESS* code, the flow finish; else if return_code is *FAIL* and error_code is not *USERPAYING*, the flow fails; else into step 6);
- 6) The return_code is *USERPAYING* means customer had to input payment password. (Whether to input the password depends on the security policy of WeChat Payment/Alipay) If customer had to input password, merchant should to hold this order and waiting for the response from Omipay server. When customer finished the payment, Omipay would call *notify_url* and send the payment information. Merchant could also call *QueryOrder* API to get the status of payment transaction.

2.5 Query Order Status

- Description:

Merchant could call this API to get the status of order.

- API address:

<https://www.omipay.com.au/omipay/api/v2/QueryOrder>

- Parameters:

Parameter	Type	Example	Description
order_no	String		Omipay Order number
language	String	EN	

- Success returns:

Field	Type	Example	Description
return_code	String	SUCCESS	SUCCESS
result_code	String	PAID	order status
out_order_no	String		The out order no value which is sent by merchant when calls pay api.
currency	String	AUD	order currency code, which is defined in ISO 4217 standard. Currently, it always be AUD.
amount	int	100	amount in order currency type. (AUD)
order_time	String		Order create time, in format of yyyyMMddHHmmss
pay_time	String		Order pay time, in format of yyyyMMddHHmmss ; If order is not payed, the field value is empty string.
exchange_rate	int		Exchange rete of order currency type(AUD) to CNY; 10 ⁸ times of real exchange rate value.
pay_currency	String	CNY	The currency no which customer actually pay.
cny_amount	int		amount in <i>pay_currency</i> .

- Fail returns:

Field	Type	Example	Description
return_code	String	FAIL	FAIL
error_code	String	SYSTEM_ERROR	Code of error
error_msg	String	服务器错误	Description of error

Error code list:

Error Code	Description
PARAMETER_INVALID	Invalid parameters.
SIGN_TIMEOUT	Time stamp expires.
MERCHANTNO_INVALID	Merchant number is invalid.
SIGN_ERROR	Signature check failed.
SYSTEM_ERROR	System unhandled error.
PERMISSION_ERROR	Permission error, Occurs when the order number is not belongs to current merchant.

- Request example:

<https://www.omipay.com.au/omipay/api/v2/QueryOrder?>

m_number=123456×tamp=1482812036067&nonce_str=313644f42ecd4758b5e23b80e86efdc4&sign=8516A3B52F9C8897F52239B19CD8A499&order_no=bc112874260946a2af2b7107825e6ce2&language=EN

- Success returns example:

```
{
  "return_code": "SUCCESS",
  "result_code": "PAYED",
  "currency": "AUD",
  "total_amount": 100,
  "order_time": "20161227105530",
  "pay_time": "20161227105602",
  "exchange_rate": 650000000,
  "cny_amount": 650
}
```

- Fail returns example:

```
{
  "return_code": "FAIL",
  "error_code": "SIGN_TIMEOUT",
  "error_msg": "Sign timeout."
}
```

- Order status list:

Status	Description
READY	Order is created, but not payed.
PAYING	Customer is now paying.
PAID	Customer is already payed.
CLOSED	Order is closed. (Settled by Omipay)
CANCELLED	Order is cancelled.
FAILED	Customer pay failed.

2.6 Payment Success Notification

- Description:

If the order is created with *notify_url* parameter, Omipay will send a request to this URL when payment success. This request would retries in 3 times unless received correct response.

- Request Rules:

Text Encoding	UTF8
Http Header	Content-Type=application/json
Data Sending Format	Data is transferred in request body, in JSON format.
Returns Data Type	application/json

- Parameters:

Parameter	Type	Example	Description
nonce_str	String		Random nonce string.
timestamp	Long		Time stamp
sign	String		Signature string.
order_no	String		Omipay order no.
out_order_no	String		Out order no.
currency	String	AUD	order currency code, which is defined in ISO 4217 standard. Currently, it always be AUD.
amount	int	100	amount in order currency type. (AUD)
order_time	String		Order create time, in format of yyyyMMddHHmmss
pay_time	String		Order pay time, in format of yyyyMMddHHmmss ; If order is not payed, the field value is empty string.
exchange_rate	int		Exchange rete of order currency type(AUD) to CNY; 10 ⁸ times of real exchange rate value.
pay_currency	String	CNY	The currency no which customer actually pay.
cny_amount	int		amount in <i>pay_currency</i> .

Notice: Merchant has to verify the sign information when receives the notification to prevent of the third-party attack.

- Merchant returns:

Field	Type	Example	Description
return_code	String	SUCCESS	Must be SUCCESS.

2.7 Refund

- Description:

Merchant could call this method to refund.

- API address:

<https://www.omipay.com.au/omipay/api/v2/Refund>

- Parameters:

Parameter	Type	Example	Description
order_no	String		Omipay Order number which is going

			to be refunded.
out_refund_no	String		Out refund no.
amount	Int		Refund amount in order currency.
language	String	EN	

- Success returns:

Field	Type	Example	Description
return_code	String	SUCCESS	SUCCESS
refund_no	String		Omipay refund bill No.
currency	String	AUD	Currency No of refund.
amount	int	100	Refund amount
refund_time	String		Refund time , in format of yyyyMMdHHmmss.

- Fail returns:

Field	Type	Example	Description
return_code	String	FAIL	FAIL
error_code	String	SYSTEM_ERROR	Code of error
error_msg	String	Server error	Description of error

Error code list:

Error Code	Description
PARAMETER_INVALID	Invalid parameters.
SIGN_TIMEOUT	Time stamp expires.
MERCHANTNO_INVALID	Merchant number is invalid.
SIGN_ERROR	Signature check failed.
SYSTEM_ERROR	System unhandled error.
PERMISSION_ERROR	Permission error, Occurs when the order number is not belongs to current merchant.
ORDER_NO_ERROR	Order No error, Occurs when the order No is wrong.
ORDER_NOT_PAID	Order is not paid.
AMOUNT_OVER_LIMIT	Refund amount is exceeds the limit.

- Request example:

<https://www.omipay.com.au/omipay/api/v2/Refund?>

m_number=123456×tamp=1482812036067&nonce_str=313644f42ecd4758b5e23b80e86efdc4&sign=8516A3B52F9C8897F52239B19CD8A499&order_no=bc112874260946a2af2b7107825e6ce2&out_refund_no=xxxxxxx&amount=100&language=EN

- Success returns:

```
{
  "return_code": "SUCCESS",
  "refund_no ": "ADDFGHJKL",
  "currency": "AUD",
  "amount": 100,
  "refund_time": "20161227105530"
}
```


- Fail returns:


```
{
  "return_code": "FAIL",
  "error_code": "SIGN_TIMEOUT",
  "error_msg": "Sign timeout."
}
```
- Additional comments:
 - 1) Refund is based on transaction, each refund bill has hooked with a specific transaction.
 - 2) An order could be refunded multiple times. The total amount of such refunds shouldn't be more than order amount.
 - 3) The api returns SUCCESS just means refund request is sent to payment platform, and the platform is accepted the request, it doesn't means the refund flow finished.

2.8 Query Refund

- Description:

Merchant should call this api to get the status of specific refund.
- API address:

<https://www.omipay.com.au/omipay/api/v2/QueryRefund>

Parameters:

Parameter	Type	Example	Description
refund_no	String		Refund no of Omipay.
language	String	EN	

Success returns:

Parameter	Type	Example	Description
return_code	String	SUCCESS	SUCCESS
result_code	String	CLOSED	status of refund.
out_refund_no	String		Out order No.
currency	String	AUD	Currency No of refund
amount	int	100	amount in order currency type.
refund_time	String		Refund create date. In formats of yyyyMMddHHmmss
success_time	String		Actually refund time. In formats of yyyyMMddHHmmss; If refund status is not CLOSED, then returns empty string.

Fail returns:

Field	Type	Example	Description
-------	------	---------	-------------

return_code	String	FAIL	FAIL
error_code	String	SYSTEM_ERROR	Code of error
error_msg	String	Server error	Description of error

Error code list:

Error code	Description
PARAMETER_INVALID	Invalid parameters.
SIGN_TIMEOUT	Time stamp expires.
MERCHANTNO_INVALID	Merchant number is invalid.
SIGN_ERROR	Signature check failed.
SYSTEM_ERROR	System unhandled error.
PERMISSION_ERROR	Permission error, Occurs when the order number is not belongs to current merchant.
REFUND_NO_ERROR	Refund No is not correct.

- Request example:

<https://www.omipay.com.au/omipay/api/v2/QueryRefund?>

m_number=123456×tamp=1482812036067&nonce_str=313644f42ecd4758b5e23b80e86efdc4&sign=8516A3B52F9C8897F52239B19CD8A499&refund_no=bc112874260946a2af2b7107825e6ce2&language=EN

- Success returns:

```
{
  "return_code": "SUCCESS",
  "result_code": "CLOSED",
  "currency": "AUD",
  "amount": 100,
  "refund_time": "20161227105530",
  "success_time": "20161227105602"
}
```

- Fail returns:

```
{
  "return_code": "FAIL",
  "error_code": "SIGN_TIMEOUT",
  "error_msg": "时间戳超时"
}
```

- Refund status list:

Status	Description
Applied	Customer is applied the refund request.
MerchantConfirmed	Merchant accepted the refund request, and submitted to payment platform.
OrganizationConfirmed	Payment platform is confirmed refund.
OrganizationPayback	Payment platform is already refunded.
Closed	Refund flow is finished, flow closed.
MerchantRejected	Merchant rejected the refund request.
TimeoutClosed	The refund request is over the time limit for refunding of this order.

OrganizationFailed	Payment platform operation failed.
CustomerCancelled	Customer cancelled refund request.

2.9 WeChat Client Login

- Description:

Omipay provided the WeChat login API, to help the merchant develops the auto login function.

- API address:

<https://www.omipay.com.au/omipay/api/auth/GetUserInfo>

- Parameters:

Parameter	Type	Example	Description
redirect_uri	String		Redirect URL of acquired user information; This URL should under URL of WESTORE type organization of this merchant.

- Success returns:

Parameter	Type	Example	Description
openid	String		OpenID of current user.
nickname	String		User' s nickname.
headimgurl	String		User' s head image URL.

- Fail returns:

Parameter	Type	Example	Description
return_code	String	FAIL	FAIL
error_code	String	SYSTEM_ERROR	Code of error
error_msg	String	服务器错误	Description of error

- Request example:

<https://www.omipay.com.au/omipay/api/v1/GetUserInfo?>

m_number=123456×tamp=1482812036067&nonce_str=313644f42ecd4758b5e23b80e86efdc4&sign=8516A3B52F9C8897F52239B19CD8A499&redirect_uri=http://yoursite.com/redirect.html